Complete Curb Products & Dynasonics Inc.
7229 Fairview St. Houston TX. 77041
P. 713-690-1622 F:713-690-1945

CCP-DPMBCLC
Double Pitched Metal Building Curb w-Loose Caps
(Peak mounted)

Standard Features:
- 18ga. G90 min. construction.

*not suggested for new construction.
- 8" min. height (12" min. with damper tray OR for package units).
- 1 1/2" rigid board (R6) insulation.
- 12" downhill flanges at both ends.
- 3 1/2" raw side flanges along the slope direction.
- Continuous welded seams coated with corrosion inhibiting compound.
- Neoprene gasket material provide for the top mounting surface.
- Cricket (water-diverter) tack welded on & caulked.
- Metal Building caps provided loose for field capping rib pocket ends.

Note: Curb I.D. is approx. 3.5" less than the O.D.



Optional Features:
1. Damper Tray.
2. 18ga. AZ55 "galvalume" construction.

*acceptable for galvalume finish roofs.
3. .080 Aluminum construction.

*acceptable for all types of roof finish.
4. 18ga. Stainless Steel, 304-2B construction.
5. Heavy gauge galvanized steel.
6. Interior metal liner (same type as exterior).
7. Extended peak flange (specify size).
8. Extended downhill flange (specify size).



Note: It is the ordering parties responsibility to verify the construction & material compliance with the panel manufacturer & the installing contractor providing the water-tightness installation.

Specification & Dimensions

Quantity	A"	B"	C"	D"	Z"	H"	Roof Slope/Pitch	Metal Building Manufacture	Metal Building Panel type	Panel Centers	Tag#	Options

All drawings are proprietary & are not to be distributed, copied or reproduced without the written consent of Complete Curb Products.