



Complete Curb Products & Dynasonics Inc.

7229 Fairview St. Houston TX. 77041

P. 713-690-1622 F:713-690-1945

CCP-GM Gasket Material

Offered in 1/4" thick x 1 1/2" wide, 25' long rolls.


Application:

Typically installed to the top mounting surface of a curb/curb adapter/curb extension/Sona-rail/etc. prior to equipment installation.

The gasket is used to seal the connection of the intended equipment onto the curb/adapter & absorbs any deviations of the surface.

Typical Physical Properties:

Color	Black
Polymer	PVC/NBR/CR
Density, lb/ft ³ , ASTM D 1667	4 - 6
25% compression deflection ASTM D-1056	2-5
50% compression set, % max, ASTM D 1056	25
Water Absorption (wt.%) max, ASTM D 1667	10
Tensile Strength, psi, min, ASTM D 412	50
Elongation, %, Min, ASTM D 412, Die A	75
Classification	
ASTM D 1056-07	2B1
ASTM D 1056-68	SBE 41
Flammability	
FMVSS 302, "0" Burn Rate	Pass
UL 94 V-0/5VA @ 6.2mm	Pass
UL 94 HF-1 @ 1.5mm	Pass
C-Tear Strength ASTM D-624 Die C, lbs/in	10 (min)
Temperature Use	
Cold Crack	-40 °F
High	200 °F



This information is furnished as a guide for selecting materials. Complete Curb Products disclaims liability for results or use of this information. It is the customer's responsibility to obtain and test samples when determining suitability of material for a particular application.

Specification & Dimensions

Quantity	Tag#